

X-band Medium-range Four-element Radar: Solid-state Coherent Pulse Doppler System With AI For All-weather Low Small Slow Target Detection And Ultra-low False Alarms

Basic Information

Place of Origin: ChinaBrand Name: MYT

Certification: CNAS、CMA、CAL、ILAC-MRA

Model Number: DD-R29Minimum Order Quantity: 1

• Price: Pricing is negotiable based on order quantity

Delivery Time: 10 work daysPayment Terms: L/C,T/T

Supply Ability: 1000units per month



Product Specification

. TAS Tracking Target Count:≥24

• Minimum Detection Altitude:≤10m

• Velocity Range: 1m/s~100m/s

• Resolution Ratio: Distance: ≤15m, Azimuth: ≤6°, Elevation:

-40 +70

≤12°

Operating Temperature

Range:

• Size: ≤861mm*861mm* 360mm

• Power Dissipation: ≤ 1000W

Supply Electricity: AC220V/DC24V

Levels Of Protection: IP66

• Joggle: RJ45 Network Port

Highlight: X-band medium-range radar,

solid-state coherent pulse Doppler radar,

anti UAV radar with AI detection

The DD-R29 medium-range X-band four-element array radar

1, Product Overview

The DD-R29 medium-range X-band four-element array radar employs a fully solid-state, fully coherent, and pulse Doppler system, enabling all-weather detection and early warning of "low, small, slow" targets. Utilizing machine learning and AI recognition technologies based on "micro-Doppler signatures" and "flight path features," the system achieves ultra-low false alarm rates while effectively detecting and classifying targets such as drones, light aircraft, helicopters, powered triplanes, airships, and airborne balloons.

2. Function

- 1) It can realize the target positioning, trajectory display and playback function on the map, and can display the target distance, azimuth, pitch and speed information;
- 2) Records and saves target track data and radar status data, and supports data playback and query;
- 3) Using Al recognition technology of "micro Doppler feature" and "track feature", it has the ability to classify and identify targets, such as drones, birds, people and cars;
- 4) Using machine learning technology, adaptive environment, no need to adjust parameters, can be started directly to work;
- 5) It has cloud and rain noise suppression function, which can work all day long;
- 6) The software can configure the pitch coverage, target update rate and range range;
- 7) It has the function of automatic compensation of independent positioning and orientation and pitch and roll angles;
- 8) It has real-time working status monitoring.

3, qualification

number parameter X frequency range 1 frequency range X frequency range 2 detection range ≥ 3Km(RCS:0.01m², unmanned aerial vehicle) 3 fade zone ≤ 100m 4 work pattern 2D Phased Array 5 hunting zone Azimuth: 0°~360°, elevation: 0°~80° (configure according to task requirements) 6 trace function TAS feature available 7 TAS tracking target count ≥ 24 8 Minimum detection altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm*360mm 20 operating temperature range -40 + 70 <t< th=""><th>order</th><th>_</th><th></th></t<>	order	_	
2 detection range ≥ 3Km(RCS:0.01m², unmanned aerial vehicle) ≥ 6Km(RCS:0.3 m², unmanned aerial vehicle) 3 fade zone ≤ 100m 4 work pattern 2D Phased Array 5 hunting zone Azimuth: 0°~360°, elevation: 0°~80° (configure according to task requirements) 6 trace function TAS feature available 7 TAS tracking target count 8 Minimum detection altitude 9 velocity range 10 Target update rate 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Tracking accuracy (RMS) 13 Tracking accuracy (RMS) 14 joggle TAS: ≤ 0.5s (default) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤0.6° 15 target capacity ≥ 500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation 20 operating temperature range -40 + 70	number	parameter	metric
2 detection range ≥ 6Km(RCS:0.3 m², unmanned aerial vehicle) 3 fade zone ≤ 100m 4 work pattern 2D Phased Array 5 hunting zone Azimuth: 0°~360°, elevation: 0°~80° (configure according to task requirements) 6 trace function TAS tracking target count 8 Minimum detection altitude 9 velocity range 10 Target update rate 11 resolution ratio 12 Search precision (RMS) 13 Tracking accuracy (RMS) 14 joggle 15 target capacity 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity 18 power dissipation 2 electrion (SMC) 2 electrion (SMC) 3 fade zone 4 york pattern 2	1	frequency range	X frequency range
4 work pattern 2D Phased Array 5 hunting zone Azimuth: 0°~360°, elevation: 0°~80° (configure according to task requirements) 6 trace function TAS feature available 7 TAS tracking target count ≥ 24 8 Minimum detection altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 861mm*861mm* 360mm 20 operating temperature range -40 + 70	2	detection range	
5 hunting zone Azimuth: 0°~360°, elevation: 0°~80° (configure according to task requirements) 6 trace function TAS feature available 7 TAS tracking target count ≥ 24 8 Minimum detection altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm*360mm 20 operating temperature range -40 + 70	3	fade zone	≤ 100m
5 hunting zone requirements) 6 trace function TAS feature available 7 TAS tracking target count ≥ 24 8 Minimum detection altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm*360mm 20 operating temperature range -40 + 70	4	work pattern	2D Phased Array
TAS tracking target count Minimum detection altitude velocity range Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° Search precision (RMS) Tracking accuracy (RMS) Minimum detection altitude TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤1° RJ45 network port target capacity ≥500 batches weight ≤ 50Kg (net equipment weight, excluding power supply/cable) Tracking accuracy (RMS) AC220V/DC24V power dissipation ≤ 1000W size ≤861mm*861mm* 360mm -40 + 70	5	hunting zone	· · · · · · · · · · · · · · · · · · ·
7 count ≥ 24 8 Minimum detection altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm*360mm 20 operating temperature range -40 + 70	6	trace function	TAS feature available
8 altitude ≤ 10m 9 velocity range 1m/s~100m/s 10 Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° 13 Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° 14 joggle RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range -40 + 70	7		≥ 24
Target update rate TWS: ≤ 3s (30° pitch coverage, 5km range) TAS: ≤ 0.5s (default) Tesolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° Harget capacity Solve a power dissipation Supply electricity AC220V/DC24V size Search precision Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° RJ45 network port ≥500 batches AC220V/DC24V AC220V/DC24V Supply electricity AC220V/DC24V Size Search precision AC220V/DC24V Search precision Search precision Ac220V/DC24V AC220V/DC24V Search precision AC220V/DC24V Search precision AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V AC220V/DC24V	8		≤ 10m
Target update rate TAS: ≤ 0.5s (default) 11 resolution ratio Distance: ≤15m, azimuth: ≤6°, elevation: ≤12° 12 Search precision (RMS) Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° RJ45 network port 15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range	9	velocity range	1m/s~100m/s
Search precision (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° RJ45 network port target capacity ≥500 batches weight ≤50Kg (net equipment weight, excluding power supply/cable) supply electricity AC220V/DC24V supply electricity power dissipation ≤1000W size ≤861mm*861mm*360mm operating temperature range	10	Target update rate	
12 (RMS) Tracking accuracy (RMS) Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1° Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° RJ45 network port 15 target capacity ≥500 batches 16 weight ≤50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤1000W 19 size ≤861mm*861mm*360mm 20 operating temperature range	11	resolution ratio	Distance: ≤15m, azimuth: ≤6°, elevation: ≤12°
Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6° RJ45 network port target capacity ≥500 batches weight ≤50Kg (net equipment weight, excluding power supply/cable) supply electricity AC220V/DC24V power dissipation ≤1000W size ≤861mm*861mm* 360mm operating temperature range	12	·	Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤1°
15 target capacity ≥500 batches 16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range	13	-	Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6°
16 weight ≤ 50Kg (net equipment weight, excluding power supply/cable) 17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range	14	joggle	RJ45 network port
17 supply electricity AC220V/DC24V 18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range -40 + 70	15	target capacity	≥500 batches
18 power dissipation ≤ 1000W 19 size ≤861mm*861mm* 360mm 20 operating temperature range -40 + 70	16	weight	≤ 50Kg (net equipment weight, excluding power supply/cable)
19 size ≤861mm*861mm* 360mm 20 operating temperature range -40 + 70	17	supply electricity	AC220V/DC24V
20 operating temperature range -40 + 70	18	power dissipation	≤ 1000W
20 -40 + 70 range	19	size	≤861mm*861mm* 360mm
21 levels of protection IP66	20		-40 + 70
	21	levels of protection	IP66

4, Application Scenarios



5, Certification Certificate



6, Company profile

Chongqing Miao Yitang Technology Co., Ltd. is a specialized company engaged in anti-drone and unmanned intelligent defense management. With the technical support from the AI Internet of Things Research Institute of the Chinese Academy of Sciences and collaborations with multiple intelligent AI companies, the company has established research laboratories for AI unmanned field products, accumulating a variety of technical patents.

The company's products are widely applied to unmanned automatic management solutions for various defense and perimeter areas, including Al anti-drone systems and Al unmanned vehicle patrol systems. These systems integrate with multiple technologies such as optoelectronics, radar, vibration, thermal imaging, facial recognition, and radio frequency management, truly achieving a 24-hour uninterrupted anti-drone defense and ground perimeter defense warning system. This allows for cost savings for clients, reduction in human resource allocation, and

ensures the safety of clients' lives and property. The outstanding security system has won the company an excellent reputation and created higher value for its partners.





7, Customer Service

- 1). We offer 24 hours service after sales
- 2). If there are any usage or quality issues with the product, we provide online technical support to diagnose the cause of the problem.

 3). Should you find the products unsatisfactory, kindly return it to us within a period of 3 months from the date of dispatch. Upon receipt and inspection, should the products be found to be free from any damage attributable to human factors, a full refund will be granted. Alternatively, we can engage in discussions to amend the product and subsequently reship the product to you.





Chongqing Miao Yi Tang Technology Co., Ltd.



+8613101235550



gary@chinaantidrone.com



chinaantidrone.com