

X-band Medium-range Phased Array Radar Solid-state Coherent Pulse Doppler System Incorporating Al Machine Learning For All-weather Detection Of Low Small Slow Targets With Minimal False Alarms

Basic Information

Place of Origin: ChinaBrand Name: MYT

Certification: CNAS、CMA、CAL、ILAC-MRA

Model Number: DD-R33Minimum Order Quantity: 1

• Price: Pricing is negotiable based on order quantity

Delivery Time: 10 work daysPayment Terms: L/C,T/T

Supply Ability: 1000units per month



Product Specification

. TAS Tracking Target Count:≥6

Minimum Detection Altitude:≤10m

• Velocity Range: 1m/s~100m/s

• Resolution Ratio: Distance: ≤15m, Azimuth: ≤6°, Elevation:

≤12°

• Operating Temperature -40 +60

Range:

• Size: ≤405mm*316mm*160mm

• Power Dissipation: ≤200W

Supply Electricity: AC220V/DC24V

Levels Of Protection: IP66

• Joggle: RJ45 Network Port

Highlight: X-band phased array radar system,

Anti UAV radar with Al detection, Solid-state coherent pulse Doppler radar

The DD-R33 medium-range X-band phased array radar

1, Product Overview

The DD-R33 medium-range X-band phased array radar employs a fully solid-state, fully coherent, and pulse Doppler system, enabling all-weather detection and early warning of "low, small, slow" targets. Utilizing machine learning and Al-based trajectory feature recognition, the system achieves highly accurate detection and classification of targets including drones, light aircraft, helicopters, powered triplanes, airships, and airborne balloons with minimal false alarm rates.

2. Function

- 1) Adaptive to the battlefield environment by using machine learning technology, which can work after installation without parameter adjustment;
- 2) Strong detection ability, low false alarm, can detect the maneuvering flight of drones;
- 3) It has cloud and rain noise suppression function, which can work all day long;
- 4) It has the directional scanning mode of "one-dimensional machine scanning + one-dimensional phase scanning" and "two-dimensional phase scanning" to realize 360° airspace and key area detection. The two modes can be flexibly switched without changing the software.
- 5) Equipped with machine scanning tracking and phase scanning TAS tracking functions.
- 6) The AI recognition technology based on "track features" can classify and identify drones, birds, people and cars;
- 7) Built-in auto-position calibration module, automatically realize auto leveling and north calibration function;
- 8) It has a range and pitch scan range setting function.

3, qualification

order		
numb	novomotov	metric
	parameter	metric
er	f.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	V fra rusana u santa
1	frequency range	X frequency range
2	detection range	≥ 3Km(RCS:0.01m ² , unmanned aerial vehicle)
		≥ 6Km(RCS:0.3 m ² , unmanned aerial vehicle)
3	fade zone	≤100m
4	work pattern	Supports machine scanning and 2D phase scanning
5	hunting zone	Scan: Angle: 0°~360°, Pitch: 0°~80° (configure according to task
		requirements)
		Sweep: Azimuth: -45° to 45°, elevation: 0° to 80° (configure according
		to mission requirements)
6	trace function	Machine scanning tracking function / phase scanning TAS function
7	TAS tracking	≥6
	target count	
8	Minimum detection	≤10m
	altitude	
9	velocity range	1m/s~100m/s
10	Target update rate	Scan duration ≤3.5 seconds per phase, with a pitch coverage of 30°
		and a range of 5 km.
11	resolution ratio	Distance: ≤15m, azimuth: ≤6°, elevation: ≤12°
12	Search precision	Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤1°
	(RMS)	
13	Tracking accuracy	Distance: ≤10m, azimuth: ≤0.4°, elevation: ≤0.6°
	(RMS)	
14	joggle	RJ45 network port
15	target capacity	≥500 batches
16	weight	≤16kg (front panel: ≤9kg, turntable: ≤12kg)
17	supply electricity	AC220V/DC24V
18	power dissipation	≤200W
19	size	≤405mm*316mm*160mm
	operating	-40 +60
20		
	temperature range	
21	levels of protection	IP66

4, Application Scenarios



5, Certification Certificate



6, Company profile

Chongqing Miao Yitang Technology Co., Ltd. is a specialized company engaged in anti-drone and unmanned intelligent defense management. With the technical support from the AI Internet of Things Research Institute of the Chinese Academy of Sciences and collaborations with multiple intelligent AI companies, the company has established research laboratories for AI unmanned field products, accumulating a variety of technical patents.

The company's products are widely applied to unmanned automatic management solutions for various defense and perimeter areas, including Al anti-drone systems and Al unmanned vehicle patrol systems. These systems integrate with multiple technologies such as optoelectronics, radar, vibration, thermal imaging, facial recognition, and radio frequency management, truly achieving a 24-hour uninterrupted anti-drone defense and ground perimeter defense warning system. This allows for cost savings for clients, reduction in human resource allocation, and

ensures the safety of clients' lives and property. The outstanding security system has won the company an excellent reputation and created higher value for its partners.





7, Customer Service

- 1). We offer 24 hours service after sales
- 2). If there are any usage or quality issues with the product, we provide online technical support to diagnose the cause of the problem.

 3). Should you find the products unsatisfactory, kindly return it to us within a period of 3 months from the date of dispatch. Upon receipt and inspection, should the products be found to be free from any damage attributable to human factors, a full refund will be granted. Alternatively, we can engage in discussions to amend the product and subsequently reship the product to you.





Chongqing Miao Yi Tang Technology Co., Ltd.



+8613101235550



gary@chinaantidrone.com



chinaantidrone.com