

# X-band Long-range Quad-cell Radar Is A Solid-state Coherent Pulse Doppler System Using Al Machine Learning For All-weather Low Small Slow Target Detection With Ultra-low False Alarms

# **Basic Information**

Place of Origin: ChinaBrand Name: MYT

Certification: CNAS、CMA、CAL、ILAC-MRA

Model Number: DD-R39Minimum Order Quantity: 1

• Price: Pricing is negotiable based on order quantity

Delivery Time: 10 work daysPayment Terms: L/C,T/T

Supply Ability: 1000units per month



# **Product Specification**

. TAS Tracking Target Count:≥24

• Minimum Detection Altitude:≤ 10m

• Velocity Range: 1m/s~100m/s

Resolution Ratio: Distance: ≤15m, Azimuth: ≤6°, Elevation: ≤4°

• Operating Temperature -40 +60

Range:

• Size: ≤ 1100mm\* 1100mm\* 750mm

Power Dissipation: ≤5500W

Supply Electricity: AC220V/DC24V

• Levels Of Protection: IP66

• Joggle: RJ45 Network Port

Highlight: X-band quad-cell radar system,

Al machine learning radar, anti-UAV long-range radar

# The DD-R39 X-band long-range quad-cell radar

### 1, Product Overview

The DD-R39 X-band long-range quad-cell radar employs a fully solid-state, fully coherent, and pulse Doppler system, enabling all-weather detection and early warning of "low, small, slow" targets. Utilizing machine learning and AI recognition based on "micro-Doppler signatures" and "flight path features," the device achieves ultra-low false alarm rates while effectively detecting and classifying targets such as drones, light aircraft, helicopters, powered triplanes, airships, and airborne balloons.

#### 2. Function

- 1) It can realize the target positioning, trajectory display and playback function on the map, and can display the target distance, azimuth, pitch and speed information;
- 2) Records and saves target track data and radar status data, and supports data playback and query;
- 3) Using AI recognition technology of "micro Doppler feature" and "track feature", it has the ability to classify and identify targets, such as drones, birds, people and cars;
- 4) Using machine learning technology, adaptive environment, no need to adjust parameters, can be started directly to work;
- 5) It has cloud and rain noise suppression function, which can work all day long;
- 6) The software can configure the pitch coverage, target update rate and range range;
- 7) It has the function of automatic compensation of independent positioning and orientation and pitch and roll angles;
- 8) It has real-time working status monitoring.

### 3, qualification

order		
number	parameter	metric
1	frequency range	X frequency range
2	detection range	≥ 10Km(RCS:0.01m <sup>2</sup> , unmanned aerial vehicle )
		≥ 20Km(RCS:0.3 m <sup>2</sup> , unmanned aerial vehicle )
3	fade zone	≤ 150m
4	work pattern	2D Phased Array
5	hunting zone	Azimuth: 0°~360°, elevation: 0°~60° (configure according to task requirements)
6	trace function	TAS feature available
7	TAS tracking target count	≥ 24
8	Minimum detection altitude	≤ 10m
9	velocity range	1m/s~100m/s
10	Target update rate	TWS: ≤ 5s (30° pitch coverage, 15km range)
		TAS: ≤ 0.5s (default)
11	resolution ratio	Distance: ≤15m, azimuth: ≤6°, elevation: ≤4°
12	Search precision (RMS)	Distance: ≤10m, azimuth: ≤0.5°, elevation: ≤0.4°
13	Tracking accuracy (RMS)	Distance: ≤10m, azimuth: ≤ 0.3°, pitch: ≤ 0.3°
14	joggle	RJ45 network port
15	target capacity	≥500 batches
16	weight	≤ 125Kg (net weight of the equipment, excluding power supply/cable)
17	supply electricity	AC220V/DC24V
18	power dissipation	≤ 5500W
19	size	≤ 1100mm* 1100mm* 750mm
20	operating	-40 +60
	temperature range	
21	levels of protection	IP66

# 4, Application Scenarios



# 5, Certification Certificate



# 6, Company profile

Chongqing Miao Yitang Technology Co., Ltd. is a specialized company engaged in anti-drone and unmanned intelligent defense management. With the technical support from the AI Internet of Things Research Institute of the Chinese Academy of Sciences and collaborations with multiple intelligent AI companies, the company has established research laboratories for AI unmanned field products, accumulating a variety of technical patents.

The company's products are widely applied to unmanned automatic management solutions for various defense and perimeter areas, including Al anti-drone systems and Al unmanned vehicle patrol systems. These systems integrate with multiple technologies such as optoelectronics, radar, vibration, thermal imaging, facial recognition, and radio frequency management, truly achieving a 24-hour uninterrupted anti-drone defense and ground perimeter defense warning system. This allows for cost savings for clients, reduction in human resource allocation, and

ensures the safety of clients' lives and property. The outstanding security system has won the company an excellent reputation and created higher value for its partners.





# 7, Customer Service

- 1). We offer 24 hours service after sales
- 2). If there are any usage or quality issues with the product, we provide online technical support to diagnose the cause of the problem.

  3). Should you find the products unsatisfactory, kindly return it to us within a period of 3 months from the date of dispatch. Upon receipt and inspection, should the products be found to be free from any damage attributable to human factors, a full refund will be granted. Alternatively, we can engage in discussions to amend the product and subsequently reship the product to you.





Chongqing Miao Yi Tang Technology Co., Ltd.



+8613101235550



gary@chinaantidrone.com



chinaantidrone.com