

UAV RID Signal Detector Remote OTA Upgrade Web-based Configuration For Unattended Fixed-site Duty

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: MYT
- Certification: CNAS、CMA、CAL、ILAC-MRA
- Model Number: KZ-40
- Minimum Order Quantity: 1
- Price: Pricing is negotiable based on order quantity
- Delivery Time: 10 work days
- Payment Terms: TT,LC
- Supply Ability: 1000units per month



Product Specification

- Detection Coverage: 400MHz-6GHz
- Probe Response Time: ≤ 1 Second (RID Signal Parsing), ≤ 2 Seconds (DID Reading)
- Resolution Distance: RID ≥ 2 Km; DID ≥ 3 Km (open Area)
- Device Power Consumption: ≤ 10 W
- Detection Range: ≥ 3 Km (open Area)
- Detection Zone: 360° Horizontal And 90° Vertical
- Detection Count: ≥ 30 Units (fixed Type)
- Working Temperature: -20°C To 65°C (Portable)
- Levels Of Protection: IP66
- Signal Capture Sensitivity: ≤ -102 dBm (2.4GHz Band), ≤ -100 dBm (5.8GHz Band)
- Highlight: UAV RID signal detector OTA upgrade, Web-based configuration UAV detector, Fixed-site anti-drone detector



More Images



for more products please visit us on chinaantidrone.com

Product Description

UAV RID Signal Detector Remote OTA Upgrade Web-based Configuration For Unattended Fixed-site Duty

1 Product Introduction

KZ-40 UAV RID signal detector supports remote OTA firmware upgrade without on-site hardware modification for unattended fixed-site duty. Operators can remotely adjust scanning bands, backhaul parameters and device running status via web-based user interface. Real-time remote monitoring covers module working conditions and power-supply voltage. On-site staff can access data and complete parameter configuration via mobile APP. The device enables convenient centralized management for large groups of geographically distributed detection terminals and greatly cuts on-site maintenance workload.



2 Specification

ORDER NUMBER	NAME	PERFORMANCE INDEX	REMARKS
1	Detection coverage	400MHz-6GHz	apolegamy
2	Signal capture sensitivity	$\leq -102\text{dBm}$ (2.4GHz band), $\leq -100\text{dBm}$ (5.8GHz band)	
3	Detection range	$\geq 3\text{ km}$ (open area)	
4	Resolution distance	RID $\geq 2\text{ km}$; DID $\geq 3\text{ km}$ (open area)	DID apolegamy
5	detection zone	360° horizontal and 90° vertical	
6	Detection display	Drone distance, flight altitude, speed, position (including latitude and longitude with precision to 1 meter), aircraft model, aircraft SN, aircraft takeoff point, aircraft return point, and real-time aircraft trajectory, etc.	
7	positioning accuracy	Broadcast accuracy consistent with UAV RID (horizontal $\leq 10\text{m}$, vertical $\leq 5\text{m}$, open environment)	
8	Detection count	≥ 30 units (fixed type)	
9	Parsing delay	$\leq 200\text{ms}$ (from signal reception to information output)	
10	Data feedback method	Supports Ethernet (10/100/1000Mbps) and 4G/5G (long-distance backhaul)	
11	working temperature	-20°C to 65°C (Portable)	

12	size	indeterminate	
13	probe response time	≤1 second (RID signal parsing), ≤2 seconds (DID reading)	
14	power supply mode	Battery-powered or mains power	
15	Device power consumption	≤10W	
16	weight of equipment	indeterminate	
17	levels of protection	IP66	

3 Functional highlight

UAV RID signal detector: Support remote OTA firmware upgrade without changing local hardware

Web-based configuration: Remotely adjust scan bands, backhaul parameters and device operating status via web UI

Real-time status monitoring: Read module working condition and supply-voltage information remotely

Local mobile-app connectivity: On-site operators view data and configure parameters through mobile application

Distributed-site friendly: Convenient centralized management for multiple detection terminals across wide regions

4 After-Sales service


Lifetime free model library upgrades, professional 24/7online service, customizable colors and languages.

5 Certification Certificate



6 Company profile

Chongqing Miao Yi Tang Technology Co., Ltd. is a cutting-edge enterprise forged through collaboration between the Internet of Things Research and Development Center of the Chinese Academy of Sciences, Sichuan University Zhisheng Software Co., Ltd. (002253), and a dedicated founding team backed by a \$12 million investment.



7 Partnership Portfolio

Our products are designed for a variety of public safety scenarios and have long provided customized product services to the military and public safety departments, earning an excellent reputation in practical operations.



8 Paking and Delivery

Supports various logistics methods including shipping, air freight, water transport, and express delivery, covering logistics in 90% of the global regions.



CUSTOMER SERVICE

- * Fast and patient communication: professional sales reply immediately
- * Fast delivery: usually 2-7 days
- * Flexible Safe shipping: fast by air or sea with cheap freight
- * Customer-friendly: complete user manual and exact video training provided
- * After sales service: one year warranty and life time technical support







Chongqing Miao Yi Tang Technology Co., Ltd.



+8613101235550



gary@chinaantidrone.com



chinaantidrone.com

www.chinaantidrone.com